



TECHNICAL DATA

O.RING	EPDM
SLIPPER	PTFE+CARBON FIBER
BUSHING	AISI 316
FILTER	700 MICRON
NOZZLES POSITIONS	4
NOZZLES SIZE	1/8"NPT
OPERATING FLOW	60 L/min
OPERATING PRESSURE	150 bar
MAX TEMPERATURE	90 °C
MATERIAL	INOX AISI 316 + BRASS + GALVANIZED STEEL
GEARS	FIXED Z=29 ROTATING Z=31
MODULE	1
FULL CYCLE	31 ROTATIONS
FULL CYCLE TIME	1.00 MIN. AT 3 BAR AIR PRESSURE
AIR MOTOR	ATLAS COPCO BA 720 INOX
WEIGHT	6.5 KG

AIR PRESSURE AND CONSUMPTION	
ROTATION SPEED	29 RPM 1 bar 264 L/min. AIR
ROTATION SPEED	42 RPM 2 bar 288 L/min. AIR
ROTATION SPEED	51 RPM 3 bar 300 L/min. AIR
ROTATION SPEED	58 RPM 4 bar 306 L/min. AIR
ROTATION SPEED	62 RPM 5 bar 312 L/min. AIR
ROTATION SPEED	66 RPM 6 bar 324 L/min. AIR

RUGOSITA' (UNI 4600) GREZZO $\sim = \phi$ SGROSS. $\nabla = 3/2$ FINITURA $\nabla \nabla = \nabla$ RETTIFICA $\nabla \nabla \nabla = 0.8/$	MODIFICA FOGLIO DATA TOLLERANZE GENERALI close m. UNI-EN 22768/1 ±0.6 6±.30 30±120 120±400 400±1000 1000±2000 ±0.1 ±0.2 ±0.3 ±0.5 ±0.8 ±1.2 NOTE: DESCRIZIONE: APPLICATION DRAWING XC 065 PPD-90°BA cm 400 mm STROKE	1 2 3 4 5	 CLEANING HEADS MONTECCHIO E. (RE) - ITALY DISIGN.: CR   CONTR.: DM DATA: 22.01.10 SCALA 1:9 A4 O	CODICE: XC 065 PPD-90°BA
--	---	-----------------------	---	-----------------------------