


TECHNICAL DATA

O.RING	EPDM
SLIPPER	PTFE+CARBON FIBRE
FILTER	700 MICRON
NOZZLES POSITIONS	2-4
NOZZLES TYPE	1/8"NPT
MAX OPERATING FLOW	60 L/min
MAX OPERATING PRESSURE	150 bar
MAX OPERATING TEMPERATURE	90 °C
MATERIAL	INOX AISI 316
CONICAL GEARS	FIXED Z=29 ROTATING Z=31
MODULE	1
COMPLETE CYCLE	31 ROTATIONS
COMPLETE CYCLE TIME	30 SEC
ROTATION SPEED	60 RPM
WEIGHT	7.5 KG

RUGOSITA' (UNI 4600)	MODIFICA	1	2	3	4	5
GREZZO	FOGLIO	XXXX				
~ = √	DATA	XX.XX.XX				
SGROSS. ∇ = √	TOLLERANZE GENERALI classe m UNI-EN 22768/1					
∇ = √	0-6	6-30	30-120	120-400	400-1000	1000-2000
	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2
	NOTE: file: XC 061 AAH cm					
FINITURA ∇∇ = √	DESCRIZIONE: APPLICATION DRAWING					
RETTIFICA ∇∇∇ = √	XC031_180°FR-AAM.01					
	DISEGN.: CR		CONTR.: DM		CODICE: XC031_180°FR-AAM.01	
	DATA: 07.05.08		MOD.		SCALA 1:2 A4 O	
	 CLEANING HEADS MONTECCHIO E. (RE) - ITALY					