



TECHNICAL DATA	
O-RING	NBR - EPDM - VITON
SLIPPER	PTFE+CARBON FIBRE
BUSHING	AISI 316
FILTER	700 MICRON
NOZZLES POSITIONS	2 - 4
NOZZLES THREAD	1/4" G
TESTING NOZZLES	0 x 0000
OPERATING FLOW RANGE	15 - 60 L/min
TESTING FLOW	00 L/min
OPERATING PRESSURE RANGE	5 - 500 bar
TESTING PRESSURE	000 bar
MAX OPERATING TEMPERATURE	90 °C
MATERIAL	INOX AISI 316
DIFUSER SPEED SETTING POSITIONS	4
TESTING DIFUSER POSITION	X
ROTATION SPEED	SEE CHART
WEIGHT	9,6 KG

FLOW L/MIN		DIFUSER POSITION			
15	13	1	2	3	4
30	6				
45	15				
60	7				
	12				
	7				
	16				
	10				
		SPINNING SPEED RPM			

RUGOSITA' (UNI 4600)	MODIFICA	1	2	3	4	5	 CLEANING HEADS MONTECCHIO E. (RE) - ITALY
GREZZO	FOGLIO DATA	XXXX					
SGROSS: 32/	TOLLERANZE GENERALI classe m UNI-EN 22768/1	XX.XX.XX					
FINITURA 1g/	0-6 ±0.1 6-30 ±0.2 30-120 ±0.3 120-400 ±0.5 400-1000 ±0.8 1000-2000 ±1.2						
RETTIFICA 0,8g/	NOTE:						
	MATERIALE:						
	DESCRIZIONE: PW 586A						
	INSTALLATION DRAWING						
	CODICE: PW 586A						
	SCALE: 1:2 A4 O						
	DISIGN.: CR1 CONTR.: DM						
	DATA: 11.05.10 MOD.						