







TECHNICAL DATA	
O-RING	NBR - EPDM - VITON
SLIPPER	PTFE-CARBON FIBRE
BUSHING	AINI 316
FILTER	700 MICRON
NOZZLES POSITIONS	2 - 4
NOZZLES THREAD	SPECIAL XB 030
TESTING NOZZLES	0 x DIA. 00.0
OPERATING FLOW RANGE	0 - 30 L/min
TESTING FLOW	00 L/min
OPERATING PRESSURE RANGE	0 - 200 bar
TESTING PRESSURE	000 bar
CENTER LINE MIN PASS THROUGH HOLE	40 mm
MANUAL MIN PASS THROUGH HOLE	40 mm
PIPE LENGTH	1018 mm (STANDARD)
MAX OPERATING TEMPERATURE	90 °C
MATERIAL	INOX AISI 316
CONICAL GEARS	FIXED Z=23 ROTATING Z=25
MODULE	1
FULL CYCLE	25 ROTATIONS
FULL CYCLE TIME	1.5 min
ELECTRIC MOTOR	BB0015
ELECTRIC MOTOR VOLT	24V AC/DC
WEIGHT	7.5 KG



RUGOSITA' (UNI 4600)	MODIFICA	1	2	3	4	5
FOGLIO	XXXX					
GREZZO	DATA	XX XX XX				
TOLLERANZE GENERALI classe m UNI-EN 22768/1						
SGROSS. 3/2	0+6	6-30	30-120	120-400	400-1000	1000-2000
∇ = 3/2	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2
NOTE:						
FINITURA 1/g	DESCRIZIONE: XB 031 E					
∇∇ = 1/g	APPLICATION DRAWING					
RETTIFICA 0,8/g						
∇∇∇ = 0,8/g						
 CLEANING HEADS MONTECCHIO E. (RE) - ITALY DISIGN.: CR ICONTR.: DM DATA: 06.07.09 CODICE: XB 031 E SCALA: 1:3 A3 O						

