



DIFFUSER POSITION	1	2	3	4
15	13	6		
30		15	7	
45			12	7
60			16	10
SPINNING SPEED RPM				

FLOW L/MIN

TECHNICAL DATA	
temperature max	90°C
pressure max	500 bar
flow	15-60 l/min
washing cycle time	4.8 min
min. pass-through hole dia.	140 mm (manual)
water inlet	1/2" G
inlet filter	700 micron
material	INOX
seals	NBR
nozzle size	1/4" NPT
nozzles positions	2 - 4
weight	9.5 Kg

RUGOSITA' (UNI 4600)	MODIFICA	1	2	3	4	5
GREZZO	FOGLIO	XXXX				
~ = \varnothing	DATA	XXXXXXXX				
SGROSS. 32/	TOLLERANZE GENERALI	close m. UNI-EN 22768/1				
∇ = ∇	0±6	6±30	30±120	120±400	400±1000	1000±2000
FINITURA 16/	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2
RETTIFICA 0g/	NOTE:					
VVV = 0g/	MATERIALE:					
	DESCRIZIONE: MW 586AA.02					
	INSTALLATION DRAWING					
	CODICE: MW 586AA.02					



DESIGN: CR | CONTR.: DM
 DATA: 16.11.06 | MOD.
 SCALA: 1:1 | A4 | 0