



TECHNICAL DATA	
temperature max	90°C
pressure max	200 bar
flow	60-200 l/min
spinning speed	15 rpm
washing cycle time	5 min
min. pass-through hole dia.	150 mm manual
water inlet	1" G
inlet filter	700 micron
nozzle size	1/4" NPT
nozzles positions	2 - 4
weight	13 Kg

RUGOSITA' (UNI 4600)	MODIFICA	1	2	3	4	5
	FOGLIO	XXXX				
GREZZO	DATA	XX.XX.XX				
	TOLLERANZE GENERALI classe m UNI-EN 22768/1	0 ÷ 6	6 ÷ 30	30 ÷ 120	120 ÷ 400	400 ÷ 1000
SGROSS.	± 0.1	± 0.2	± 0.3	± 0.5	± 0.8	± 1.2
▽ = 3.2/	NOTE: VERS. 02					
FINITURA	MATERIALE:					
▽▽ = 1.6/	DESCRIZIONE: APPLICATION DRAWING					
RETTIFICA	RW 200 A					
▽▽▽ = 0.8/	CODICE:					
	1:1	A3	0			
	SCALE		MONTECCHIO E. (RE) - ITALY			
	DATA: 25.10.07		DISEGN.: CR CONTR.: DM			
			MOD.			
			MW 200A			



CLEANING HEADS

MONTECCHIO E. (RE) - ITALY