



APERTURA DIFFUSORE DIFFUSER OPENING				
PORTATA FLOW L/MIN	3	3/6	3/6/9	3/6/9/12
60	12	8		
80	16	12	9	
100		15	11	
120		18	13	11
140			16	13
160			18	14
180				16
200				16

  

VELOCITA' ROTAZIONE GIR/MIN SPINNING SPEED RPM	
	16

PRESSIONE PRESSURE RANGE	5#200 BAR
PORTATA FLOW	60#200 L/MIN
TEMPERATURA MAX MAX TEMPERATURE	90°C
MATERIALE MATERIALS	AINI 316 INOX STAINLESS STEEL
PESO WEIGHT	9.6 KG

CICLO COMPLETO IN 73 GIRI  
COMPLETES PATTERN IN 73 ROTATIONS

NUMERO UGELLI NOZZLES POSITIONS	2 - 4
FILETTO UGELLI NOZZLES THREAD	1/4"NPT

RUGOSITA' (UNI 4800)	MODIFICA 1	2	3	4	5	 <b>Bolonardi</b> CLEANING HEADS MONTICCHIO E. (RE) - ITALY DATA: 16.01.08 MOD. SP4A	
GREZZO	FOGLIO	XXXX					
~	DATA	XX.XX.XX					
∅	TOLLERANZE GENERALI close m. UNI-EN 22768/1						
SGROSS: 3.2/	0+6	6+30	30+120	120+400	400+1000		1000+2000
∇ = 3.2/	±0.1	±0.2	±0.3	±0.5	±0.8		±1.2
∇ = 1.6/	MATERIALE:						
RETTIFICA 0.8/	DESCRIZIONE: INSTALLATION DRAWING RW 200AW						
∇∇∇ = 0.8/	CODICE: RW 200AW						
	1:1 A3 0						