


TECHNICAL DATA

O-RING	NBR-EPDM-VITON
SUPPLIER	PTFE+CARBON FIBER
FILTER	700 MICRON
NOZZLES POSITIONS	2 - 4
NOZZLES SIZE	1/8"NPT
OPERATING FLOW	MAX 60 L/min
OPERATING PRESSURE	MAX 200 bar
MAX TEMPERATURE	90 °C
MATERIAL	INOX AISI 316
FULL CYCLE	31 ROTATIONS
FULL CYCLE TIME	1.00 MIN. AT 3 BAR AIR PRESSURE
WEIGHT	4.9 KG

AIR PRESSURE AND CONSUMPTION

ROTATION SPEED	29 RPM	1 bar	264 L/min. AIR
ROTATION SPEED	42 RPM	2 bar	288 L/min. AIR
ROTATION SPEED	51 RPM	3 bar	300 L/min. AIR
ROTATION SPEED	58 RPM	4 bar	306 L/min. AIR
ROTATION SPEED	62 RPM	5 bar	312 L/min. AIR
ROTATION SPEED	66 RPM	6 bar	324 L/min. AIR

RUGOSSITA' (UNI 4600)	MODIFICA	1	2	3	4	5
GREZZO	FOGLIO	xxxx				
~ = ϕ	DATA	xx.xx.xx				
SGROSS = $3/2$	TOLLERANZE GENERALI classe m UNI-EN 22768/1					
∇ = $1/8$	0+6 -1 6+30 30+120 120+400 400+1000 1000+2000					
FINITURA $1/8$	±0.1 ±0.2 ±0.3 ±0.5 ±0.8 ±1.2					
RETTIFICA $0/8$	NOTE:					
$\nabla\nabla = 1/4$	MATERIALE: INOX					
$\nabla\nabla\nabla = 1/2$	DESCRIZIONE: APPLICATION DRAWING					
	XC 031_180FR-PPD.01					
	CODICE: XC 031_180FR-PPD.01					
	 CLEANING HEADS MONTICCHIO E. (RE) - ITALY DISIGN.: CR I CONTR.: DM DATA: 27.10.09 MOD. scala 1:2 A3 0					