


MAX FLOW	600 L/min.
MAX PRESSURE	10 bar
NOZZLES POSITIONS	2
NOZZLES SIZE	7.5-11-14-15.5 mm
DRIVE	REACTION
ROTATION SPEED	5 to 10 rpm
SPEED CONTROL	AERODYNAMIC
MATERIAL	INOX AISI 316
BUSHING MATERIAL	PEEK
MIN PASS THROUGH HOLE	900 mm
WEIGHT	7.5 Kg.

RUGOSITA' (UNI 4600)	MODIFICA	1	2	3	4	5	 CLEANING HEADS MONTECCHIO E. (RE) - ITALY
GREZZO	FOGLIO						
SGROSS.	DATA	TOLLERANZE GENERALI classe m UNI-EN 22768/1					DISIGN.: CR CONTR.: DM DATA: 03.06.10 MOD.
$\nabla = \varphi'$		0±6	6±30	30±120	120±400	400±1000	
FINITURA $\nabla \nabla = 1.6/\nabla$	MATERIALE:	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2
RETTIFICA $\nabla \nabla \nabla = 0.8/\nabla$	DESCRIZIONE: INSTALLATION DRAWING PW 610	NOTE:					CODICE: PW 610 cm