



TECHNICAL DATA

O-RING	NBR - EPDM - VITON
SLIPPER	PTFE+CARBON FIBRE
BUSHING	AIISI 316
FILTER	700 MICRON
NOZZLES POSITIONS	4
NOZZLES THREAD	1/4" G
OPERATING FLOW RANGE	15 - 60 L/min
OPERATING PRESSURE RANGE	5 - 200 bar
MAX OPERATING TEMPERATURE	90 °C
MATERIAL	INOX AISI 316
ORBITAL GEARS	FIXED Z=128 ROTATING Z=16
MODULE	2
DIFFUSER SPEED SETTING POSITIONS	4
ROTATION SPEED	SEE CHART
FULL CYCLE	1 ROTATION
FULL CYCLE TIME	5 seconds AT 12 RPM
WEIGHT	9,6 KG

PORTATA FLOW L/MIN
15
30
45
60

POSIZIONE DIFFUSORE DIFFUSER POSITION
1
2
3
4

RUGOSITA' (UNI 4600)	MODIFICA	1	2	3	4	5
GREZZO	FOGLIO	XXXX				
~ = <math>\phi</math>	DATA	XXX.XX.XX				
SGROSS: <math>\nabla</math> = <math>3/2</math>	TOLLERANZE GENERALI classe m UNI-EN 22768/1	0±6	6±30	30±120	120±400	400±1000
<math>\nabla</math> = <math>3/2</math>	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2
FINITURA <math>\nabla</math> = <math>1/6</math>	MATERIALE:					
RETTIFICA <math>\nabla</math> = <math>0,8</math>	DESCRIZIONE: INSTALLATION DRAWING PW086A					
	codice:					
	1:2	A3	0			
	DM					
	DISIGN.: GR I CONTR.: DM					
	DATA: 09.07.14					
	MOD.					
	PW086A					

